

MONO BAND GPS ANTENNA

1575.42 MHz

MLV-R

TRANSPORT

POLOMARCONI offers a very wide range of wireless products. Our products can be tailored according to the customer's need.

Electrical Specifications

SATELLITE NAVIGATION AND GEOLOCALIZATION BAND

Frequency band (MHz)	1574.42 ÷ 1576.42
Impedance (Ω)	50
Polarization	Right Hand Circular Polarization (RHCP)
Gain (dBic)	\geq 25 (typical 27), @T ₀ =25°C, V _{DC} =5V
Noise Figure (dB)	\leq 2.5, @T ₀ =25°C, V _{DC} =5V
Operating supply voltage (V_{DC})	3 ÷ 7
Current consumption (mA)	\leq 35, @T ₀ =25°C, V _{DC} =5V
Satellite navigation and geolocalization supported systems	



Mechanical Specifications			
Connector			TNC f
Dimensions (Height from installation surface x Base diameter, mm) 32.5 \times ø75			
Weight (kg)			0.3
Materials Ra Conne	dome	Aluminium with SURTEC 650 High im	galvanic treatment pact polycarbonate Silver plated brass
Mounting		at the center of a metallic with a minimum s	conductive surface size of 250x250mm
Reliability (hours)			> 200,000

Environmental Specifications ATMOSPHERIC and CLIMATIC CONDITIONS according to NF EN 60068 -40°C, +70°C Temperature conditions Atmospheric pressure -40°C, +70°C, 95% HR at 2000 m Rain, hail, snow, frost 1000 mm/h, 1 J impact, 0.5 m, 3 cm Combined wind and train speed 530 km/h MECHANICAL CONDITIONS according to NF EN 60068, 61373 and 15-818 Free falls Hits (vertical, cross-sectional, longitudinal) 30m/s², 30m/s², 50m/s², 30ms **Impacts** 50 J RoHS 2011/65/EU compliant FLAMMABILITY RATING according to EN 45545-2 IP rating: IP67

MOUNTING FLANGE

Mounting: for the optimal performance we suggest at the center of a metallic conductive surface with a minimum size of 250x250mm; for different ground plane dimensions see page 2; it's advisable to keep the mounting surface clean and free from paint for an optimal electrical contact.

Mounting with a drilling hole of 16.5 mm of diameter



MONO BAND GPS ANTENNA


1575.42 MHz

MLV-R

TRANSPORT

POLOMARCONI offers a very wide range of wireless products.
Our products can be tailored according to the customer's need.

DRILLING MASK



All dimensions are in mm