



6 CH UHF RX SINGLE CAVITY COMBINER

in Star Point Configuration

T06120673

POLOMARCONI.IT

POLOMARCONI offers a very wide range of wireless products.
Our products can be tailored according to the customer's need.

ATC



Electrical Specifications

Frequency band (MHz)	225 ÷ 400
Impedance (Ω)	50
Max Continuous Power (W) per channel	100
Return Loss (dB)	≥ 15
I.L. (dB) @ ch. spacing:	@ $f_0 \pm 1\% f_0$ 2
Isolation (dB) @ ch. spacing:	@ $f_0 \pm 1\% f_0$ > 19
Filter Selectivity (dB) at mid band with I.L. : 1 dB	@ $f_0 \pm 1\% f_0$ > 18 @ $f_0 \pm 2\% f_0$ > 24
Electrical Safety	IEC 60950-1 EN 60950-1
Operating Environment	ETS 300 019-1-2 ETS 300 019-2-3 Class 3.1E
EMC	ETSI EN 301 489-1 489-22

Mechanical Specifications

RF Connectors	Nf
Dimensions (mm)	6U x 19" x 650
Weight (kg)	< 18
Colour	RAL 9011
Operating Temp. Range (°C)	-10 ÷ +55

Electric Schematics



DIMENSIONS (mm)

