

GSM-R DUPLEXER RACK MOUNTING SX

876 ÷ 890 / 921 ÷ 925 MHz

T06210947

RAILWAYS AND TRANSPORT





POLOMARCONI offers a very wide range of wireless products Our products can be tailored according to the customer's need

Electrical Specifications					
Impedance (Ω)	50				
Isolation (dB)	≥ 70				
Max. Continuous Power (dBm) at any port	40				
Operating Temp. Range (°C)	-25 ÷ +70				
Up-Link (TX) Section					
Frequency Band (MHz)	876 ÷ 890				
Insertion Loss (dB)	≤ 1.3 (typical : 0.7)				
Return Loss (dB)	≥ 18 (typical : 20)				
Rejection (dB) of the RX section	≥ 70				
Down-Link (RX) Section					
Frequency Band (MHz)	921 ÷ 925				
Insertion Loss (dB)	Max: ≤ 3 (typical : 2.6)				
Return Loss (dB)	≥ 15 (typical : 20)				
Rejection (dB) @ 926.5 MHz	≥ 30				



Mechanical Specifications Antenna connector (RF2) N female Down-link RX connector (OUT2) TNC female Up-link TX connector (IN2) TNC female Dimensions (mm) 287.50 × 106.38 × 128.40 Weight (kg) < 2.3 Material Alluminium alloy Finishing Silver plating





CEI EN61373 cat.1 class B

34

Dimensions (mm)

Vibrations

MTBF (years)






GSM-R DUPLEXER RACK MOUNTING SX

876 ÷ 890 / 921 ÷ 925 MHz


T06210947

RAILWAYS AND TRANSPORT

POLOMARCONI offers a very wide range of wireless products. Our products can be tailored according to the customer's need.



-1		50.000 MHz	-50 Stop: 960.000 MHz	
Mkr	Trace	X-Axis	Value	Notes
1	S11	876.000 MHz	-28.600 dB	>= 18 dB
2	S13	876.000 MHz	-0.412 dB	<= 1.3 dB
3 ₹	S33	876.000 MHz	-27.837 dB	>= 18 dB
4 ₹	S11	890.000 MHz	-26.258 dB	>= 18 dB
5	S13	890.000 MHz	-0.450 dB	<= 1.3 dB
6 Д	S33	890.000 MHz	-28.760 dB	>= 18 dB
8 ₹	S13	921.000 MHz	-76.204 dB	>= 70 dB
11 🎖	S13	925.000 MHz	-77.657 dB	>= 70 dB



Mkr	Trace	X-Axis	Value	Notes
1 ₹	S11	921.000 MHz	-24.792 dB	>= 15 dB
2	S21	921.000 MHz	-1.229 dB	<= 3.0 dB
3 ₹	S22	921.000 MHz	-20.965 dB	>= 15 dB
4 ₹	S11	925.000 MHz	-19.950 dB	>= 15 dB
5	S21	925.000 MHz	-2.316 dB	<= 3.0 dB
6 △	S22	925.000 MHz	-25.797 dB	>= 15 dB
8 ₹	S21	876.000 MHz	-89.511 dB	>= 70 dB
11 🏹	S21	890.000 MHz	-75.109 dB	>= 70 dB
13 🏹	S21	927.413 MHz	-30.475 dB	>= 30 dB