



THREE BAND UHF*- GSM/R - GPS ANTENNA

440 ÷ 470 , 876 ÷ 960 and 1575.42 MHz

TRGLD

POLOMARCONI.IT

POLOMARCONI offers a very wide range of wireless products. Our products can be tailored according to the customer's need.

TRANSPORT

Electrical Specifications

Frequency band (MHz)	440 ÷ 470 876 ÷ 960
Impedance (Ω)	50
VSWR	<1.7
Continuous Max. Power (W)	30
Polarization	vertical
Gain (dB) over $\lambda/4$ monopole	0
Operating Temp. Range ($^{\circ}\text{C}$)	-40 ÷ +70

GPS BAND

Frequency band (MHz)	1575.42 \pm 1
Impedance (Ω)	50
VSWR (GPS antenna without amplifier mounted on a conductive surface of dimensions 5x5 cm)	<1.5
Medium gain (dBic) (GPS antenna without amplifier) at zenith (90° of elevation)	-2 ÷ +1
Polarization	right hand circular

GPS AMPLIFIER

Gain (dB)	> 27 (29 medium)
Noise factor (dB)	< 1.5 (1.2 medium)
Power supply (V)	5 \pm 40%
Consumption (mA)	23 \pm 3.5 (21 medium)



Patent n° 1548873

Antenna for train with protective means against high voltages.

Patent has been used by SNCF and by the most important producers of trains.



Mechanical Specifications

Connectors	N female for UHF and GSM/R TNC female for GPS (SMA female for 3V model)
Dimensions (mm)	140x80x145
Weight (kg)	0.5
Materials	Connectors: Silver plated brass Base: Aluminium with SURTEC 650 treatment Radome: High impact polycarbonate
Mounting	on metallic surface (600x600 mm minimum)
Reliability	above to 200,000 hours

Environmental Characteristics

ATMOSPHERIC and CLIMATIC CONDITIONS according to NF EN 60068

Temperature conditions	-40 $^{\circ}\text{C}$, +70 $^{\circ}\text{C}$
Atmospheric pressure	-40 $^{\circ}\text{C}$, +70 $^{\circ}\text{C}$, 95% HR at 2000 mt
Rain, hail, snow, frost	1000 mm/h, 1 J impact, 0.5 m, 3 cm
Combined wind and train speed	530 km/h

MECHANICAL CONDITIONS according to NF EN 60068, 61373 and 15-818

Free falls	1 m
Hits (vertical, cross-sectional, longitudinal)	30m/s ² , 30m/s ² , 50 m/s ² , 30ms
Impacts	50 J

GROUNDING and HIGH VOLTAGE PROTECTION according to NF EN 50388 and NF EN 50123

Short-circuit currents flow / time before breaking	70 kA / 5 ms – 40 kA / 100 ms (DC) 31,5 kA / 10 ms – 15 kA / 100 ms (AC)
--	---

MOUNTING FLANGE

Mounting: on a conductive surface with a minimum size of 600x600 mm; it's advisable to keep the mounting surface clean for a better electrical contact. TRGLD 4 holes flange: flange with 4 M10 studs included.

Grounding and high voltage protection: Our antennas have passed the strict SNCF's tests that approved our products as protected against lightning and high-tension voltage thanks to our patented DC and AC grounded system.

Advantage: amplifier included; there is no need of an external low noise GPS amplifier as the internal GPS signal is already amplified.

***Advantage:** UHF frequency could be modified on customer's request

Approved by: SNCF, SNCB, TRENITALIA